


DRAKO P 502



Type of lay	ordinary lay
Direction of lay	right, alternatively left
Core	steel core
Number of outer strands	12
Number of load bearing wires in the outer strands	84
Surface of wire	galvanized (B), alternatively bright (U)

Characterisation	rotation resistant
Applications	electric hoist, towercrane
Discard criteria determined according to DIN 15020 part 2, ISO 4309	



WARNING! Never use a Swivel!
Failure may cause serious personal injuries or material damages

Nominal rope-Ø -0 +5 % mm	Approx. mass kg/100m	Minimum breaking force/rope grade		
		kN/1960	kN/2060	kN/2160
6,0	15,0	26,0	28,7	29,1
6,7	18,4	33,6	35,3	37,0
7,0	20,8	36,7	38,5	40,4
8,0	28,0	45,8	50,4	54,8
9,0	31,9	58,5	64,5	64,9
10,0	40,7	71,7	79,0	82,0
10,5	44,0	79,0	87,1	88,4
11,0	51,0	88,2	97,1	101,0
12,0	58,0	107,4	118,3	114,8
13,0	69,0	122,2	134,7	142,0
14,0	83,0	141,1	155,5	165,0
16,0	111,0	190,7	210,1	223,0
18,0	130,0	234,5	258,4	264,0